

TOOLBOX SAFETY TALK



INTRODUCTION

1. Review any accidents or “near accidents” from the past week.
2. Describe the hazards of the work as they relate to your project. Explain or show the SAFE way of doing the job.
3. Give the TOOLBOX SAFETY TALK.

RIGGING 2

Rigging appears to be an easy operation that does not seem to require any particular skill or experience. Don't be fooled. Many people have lost fingers or hands, or suffered more serious damage.

To avoid injuries at work, follow these rules:

BE SURE OF YOUR SIGNALS

- Appoint a team member to act as signal person and order the crane operator not to accept signals from just anyone.
- The signal person should not request a movement until getting an “all set” from each team member.
- All workers must be in the clear before giving the “all set” to the signal person.
- If you have to hold onto the chain, sling, or air regulator that keeps the tension, be sure that your hands and feet are removed from pinch points before giving the “all set.”
- Check for obstructions and power lines above you.

PROTECT YOUR HANDS.

- If you cannot let go of the chain, sling, or air regulator, be sure your hands are away from the pinch points.
- Keep your hands far enough away so that a frayed wire or splinter in the cable cannot catch your glove and yank your hand into a pinch point.

BE ALERT FOR SWINGING AND ROLLING

- It is virtually impossible to position the hook exactly over the center of the load. Be on the lookout for swinging and rolling.
- Anticipate the direction of the swing or roll and work far away from it.

TOOLBOX SAFETY TALK



- Never stand between the material, equipment or other stationary objects and the load.
- Stay far away from material piles which may collapse due to a pivoting load.
- Stay away from the area under a load.
- Never stand under a suspended load.
- Keep out of the area under the crane's boom.

POSITION IT CAREFULLY

- When a load has to be guided, use a tag line or hook it.
- If you have to travel with a load, keep the load as close to the ground as long as possible.
- Examine the point where the load should be positioned. Remove unnecessary blocks or other objects that could fly up when they are pushed by the load.
- When lowering or setting a load, keep your feet and the rest of your body parts in the clear.
- Set the load on the ground easily and slowly. If you rotate on the block, it will change position slowly and you will be able to get out of the situation.

REMINDER: TEAMWORK IS IMPORTANT IN ANY JOB TO PREVENT DAMAGE TO YOURSELF AND TO OTHERS.

TOOLBOX SAFETY TALK



INTRODUCCIÓN:

1. Revise cualquier accidente o “casi accidentes” de la semana pasada.
2. Describa los peligros del trabajo en relación con su proyecto. Explique o muestre la forma SEGURA de hacer el trabajo.
3. Presenta la platica “TOOLBOX SAFETY TALK” caja de herramientas de seguridad.

APAREJO 2

Aparejar parece una operación fácil que no parezca requerir ninguna habilidad o experiencia particular. No se engañe. Mucha gente ha perdido los dedos o las manos o sufrido perjuicios más serios.

Para evitar perjuicios en el trabajo, siga estas reglas: ESTE SEGURO DE SUS SEÑALES

- Designe a un miembro del equipo que actúe como persona de la señal, y mande al operador de grúa que no acepte señales de cualquier persona
- La persona de la señal no debe pedir un movimiento hasta conseguir el “todo listo” de cada miembro del equipo.
- Cada trabajador debe estar en el claro antes de dar el “todo listo” a la persona de la señal.
- Si usted debe aferrarse al encadenamiento, la honda, o al regulador de aire que mantiene la tensión, este seguro que sus manos y pies estén retiradas de puntas de apretones antes de dar el “todo listo”.
- Revise por obstrucciones y líneas de potencia por encima de su persona.

PROTEJA SUS MANOS.

- Si no es posible soltar el encadenamiento, la honda, o el regulador de aire, este seguro que sus manos estén retiradas de los puntos de apretones.
- Mantenga sus manos basta lejos de modo que un alambre o una astilla raído en el cable no pueda coger su guante y mover de un tirón su mano en una punta de apretón.

ESTE ALERTO POR OSCILACIONES Y RODILLOS.

- Es casi imposible colocar el gancho exactamente sobre el centro de la carga. Este pendiente por oscilación y rodillos.
- Anticipe la dirección del oscilación o rueda y trabaje lejos de él.
- Nunca se coloque entre el material, equipo u otros objetos inmóviles y la carga.

TOOLBOX SAFETY TALK



- Permanezca lejos del material en pilos que se puede derrumbar por una carga pivotando.
- Permanezca retirado de la area debajo de una carga.
- Nunca se ponga debajo de una carga suspendida. • Mantengase fuera de la area debajo del ague de la grúa.

PONGALO EN POSICIÓN CUIDADOSAMENTE

- Cuando sea necesario guiar una carga, utilice una línea de etiqueta o engánchela.
- Si usted tiene que recorrer con una carga, mantenga la carga cerca de la tierra cuanto mas pueda.
- Examine el punto donde la carga debe ser posicionada. Quite los bloques innecesarios u otros objetos que pudiesen volar asi arriba cuando sean pulsados por la carga.
- Cuando este bajando o fijando una carga, mantenga sus pies y el resto de las partes de su cuerpo en el claro.
- Fije la carga en la tierra fácilmente y lentamente. Si rueda en el bloque, cambiará de puesto lentamente y usted podrá retirarse de la situación.

RECORDATORIO - EL TRABAJO EN EQUIPO ES IMPORTANTE EN CUALQUIER TRABAJO DE PREVENIR PERJUICIO ASI USTED MISMO Y A LOS DEMAS.